

SR 68-LED

Recessed Swivel and Tilt LED Luminaire



Article No.	Description	Illustration	Features	Weight	
202 024 002 01	SR 68-LED 4,8W 22° ww matt chrome		<ul style="list-style-type: none"> • Colour appearance ww (warm white) approx. 3000 K • supply cable 0.2 m with LED 350 plug • beam angle 22° or 35° 	110 g	
202 024 012 01	SR 68-LED 4,8W 35° ww matt chrome			110 g	
202 024 015 01	SR 68-LED 4,8W 35° ww white			110 g	
202 024 003 01	SR 68-LED 4,8W 22° nw matt chrome			<ul style="list-style-type: none"> • Colour appearance nw (neutral white) approx. 4000 K • supply cable 0.2 m with LED 350 plug • beam angle 22° or 35° 	110 g
202 024 013 01	SR 68-LED 4,8W 35° nw matt chrome				110 g
202 024 016 01	SR 68-LED 4,8W 35° nw white				110 g
610 014 702 01	SR 68-LED Set 9,6W 22° ww matt chrome		<ul style="list-style-type: none"> • Colour appearance ww (warm white) approx. 3000K • beam angle 22° or 35° • incl. LED transformer with mains cable 2 m with Euro plug • dimmable version on request 	380 g	
610 014 712 01	SR 68-LED Set 9,6W 35° ww matt chrome			380 g	
610 014 715 01	SR 68-LED Set 9,6W 35° ww white			380 g	
610 014 703 01	SR 68-LED Set 9,6W 22° nw matt chrome			<ul style="list-style-type: none"> • Colour appearance nw (neutral white) approx. 4000 K • beam angle 22° or 35° • incl. LED transformer with mains cable 2 m with Euro plug • dimmable version on request 	380 g
610 014 713 01	SR 68-LED Set 9,6W 35° nw matt chrome				380 g
610 014 716 01	SR 68-LED Set 9,6W 35° nw white				380 g
205 010 214 06	Adapter ring SR 68 round matt chrome		<ul style="list-style-type: none"> • for mounting in drill holes up to 84 mm 	12 g	
205 010 214 01	Adapter ring SR 68 round white			12 g	
205 010 214 16	Adapter ring SR 68 square matt chrome			29 g	
205 010 214 11	Adapter ring SR 68 square white			29 g	
215 250 610 01	LED 350 Connecting cable 1m		<ul style="list-style-type: none"> • further information on page 147 	12 g	
215 250 620 01	LED 350 Connecting cable 2m			20 g	
206 040 027 01	Transformer LED 350/5W with one socket		<ul style="list-style-type: none"> • for 1 SR 68-LED • Mains cable 0,3 m with ferrules (for easy ceiling suspension on 230 V) • further information on page 144 	50 g	
615 003 009 03	Transformer LED 350/9W 3-way distributor with Euro plug		<ul style="list-style-type: none"> • for 1 – 2 SR 68-LED • further information on page 144 	175 g	
615 003 009 43	Transformer LED 350/16W 3-way distributor		<ul style="list-style-type: none"> • for 3 SR 68-LED • further information on page 145 	200 g	
615 003 009 45	Transformer LED 350/16W 5-way distributor			<ul style="list-style-type: none"> • for 4 SR 68-LED • further information on page 145 	210 g
615 003 009 28	Transformer LED 350/2x9W dim 2 x 3-way distributor		<ul style="list-style-type: none"> • for 4 SR 68-LED (on page 146) • dimmable 1-10 V • mains cable 2 m with Euro plug • dim control cable 0.2 m with Mini AMP plug 	220 g	
506 180 401 01	Mounting dimmer switch (1-10V)		<ul style="list-style-type: none"> • dimmer cable 2 m with Mini AMP-socket • further information on page 139 	95 g	

New

New

New